

DOWNLIGHTS / SURFACE MOUNTED / LOW GLARE / PHILIPS

Crown

Lightweight spun-aluminium professional LED surface downlight with outputs up to 3125 llm.

Crown is a professional LED surface downlight. It uses an integral Philips LED and driver system, RAL9016 brilliant white as standard, a low-glare multi-faceted reflector, ETL-compliant efficacies up to 133 llm/tcW, MacAdam colour tolerance below 3 SDCM, and integral DALI, wireless and emergency options.

The compact form and reliable thermal design make it suitable for long-life commercial schedules. It supports controlled project delivery where low-glare quality and accessory flexibility matter.



<p>Surface downlight Lightweight spun-aluminium surface-mounted body for commercial interiors.</p>	<p>Philips system Integral Philips LED and driver system.</p>	<p>Low-glare reflector Multi-faceted reflector listed as standard for controlled downlighting.</p>	<p>Up to 133 llm/tcW ETL-compliant efficacies up to 133 llm/tcW.</p>	<p>>60,000h L80/B10 Long-life performance for commercial schedules.</p>	<p><3 SDCM MacAdam colour tolerance below 3 SDCM.</p>
---	--	---	---	---	---

Key Features

- + Lightweight spun-aluminium surface-mounted body for commercial interiors.
- + Multi-faceted reflector listed as standard for controlled downlighting.
- + Long-life performance for commercial schedules.
- + Integral emergency and DALI emergency options listed for specification options.
- + Lumen output range: 1200-3125 llm
- + Integral Philips LED and driver system.
- + ETL-compliant efficacies up to 133 llm/tcW.
- + MacAdam colour tolerance below 3 SDCM.
- + Proudly made in the UK.
- + Power consumption: 9.5-24.0 W

Dimensions

PRODUCT DRAWING

203 MM DIAMETER, 165 MM HEIGHT

Diameter	Height
203 mm	165 mm

Ordering Information

COLOUR TEMP	LUMINAIRE OUTPUT	POWER (TCW)	MODEL REF.
3000K	1200 llm	9.5 W	15.001
4000K	1250 llm	9.5 W	15.002
3000K	1900 llm	15.0 W	15.003
4000K	2000 llm	15.0 W	15.004
3000K	2950 llm	24.0 W	15.005
4000K	3125 llm	24.0 W	15.006

Options

CONTROLS /T+DALI, /BTC	EMERGENCY /EMI, /EMDI	PERFORMANCE / BODY /R9, /SA65
ACCESSORIES / FINISHES RAL9016, PV, Surface	PRODUCT VARIATIONS PV, /SA65	

Controls, options and accessories

Specification options, accessories and product variations for the Crown family.



MADE IN THE UK

REV3 / MAY 2026

LL-CROWN-15-DS





Options

 <p>/BK Black - RAL 9005</p>	 <p>/GY Grey - RAL 9006</p>	 <p>/WH Soft white - RAL 9010</p>	 <p>/SA65 65° satin etched reflector</p>	 <p>Touch Dimming OR DALI 2 /T+DALI Touch dimming or DALI control gear</p>
 <p>/BTC Casambi wireless network inc. dimming</p>	 <p>/EMI Emergency Integral ILEM</p>	 <p>/EMDI DALI / Self test EM Integral ILEM</p>	 <p>/R9 High colour rendering Premium White LED</p>	 <p>/SUS 2 m suspension kit with mounting plate</p>
 <p>/SUS.B 2 m suspension kit</p>	 <p>BTWS001 Wireless Casambi single wall switch</p>	 <p>BTWS002 Wireless Casambi twin wall switch</p>		

PV - Product Variations



PV - Contact Sales
Any RAL colour

				DC	Declaration of Conformity available
---	---	---	---	-----------	-------------------------------------

Please note: Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25 deg C. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/-10%. We reserve the right to amend or change details without prior notification. E5DE.