

TRACK SPOTLIGHTS / ADJUSTABLE BEAM / VOSSLÖH

Iris Track

Track-mounted LED spotlight with adjustable 15 deg to 55 deg beam control.

Iris Track is listed as an OptiFlex track-mounted spotlight with a rotatable optical-modification bezel and flexible beam adjustment from 15 deg to 55 deg.

The source file lists white as standard with black option, Ra90 availability, Vossloh LED and in-track driver system, and DALI, mains dimming and wireless control options.



<p>15 to 55 deg beam Flexible beam angle adjustment is listed on the source file.</p>	<p>Track control options The source sheet lists /MDIM, /DALI and /BTC.</p>	<p>L90 at 55,000 hours Lumen maintenance is listed as L90 at 55,000 hours.</p>	<p>Made in the UK The source sheet carries Made in the UK marking.</p>
--	---	---	---

Key Features

- + OptiFlex LED track-mounted spotlight
- + Flexible beam angle from 15 deg to 55 deg
- + Vossloh LED and in-track driver system
- + MacAdam colour tolerance 3 SDCM
- + 5 year warranty
- + Rotatable optical-modification bezel
- + Finished in white as standard with black option
- + Ra80 with Ra90 option
- + DALI and wireless control options

Technical Drawing



Length 158 mm to 250 mm	Diameter Dia 64 mm
Body 130 mm	Overall height 193 mm
Rotation 90 deg	

Ordering Information

OUTPUT (LLM)	COLOUR	POWER (TCW)	EFFICACY (LLM/TCW)	MODEL REF.
925	3000K	11.0	84	IRISTRACK.001/L0
950	4000K	11.0	86	IRISTRACK.002/L0
1125	3000K	14.0	80	IRISTRACK.001
1150	4000K	14.0	82	IRISTRACK.002
1450	3000K	20.5	70	IRISTRACK.003
1475	4000K	20.5	72	IRISTRACK.004
1675	3000K	26.5	63	IRISTRACK.005
1725	4000K	26.5	64	IRISTRACK.006

Options

FINISH /BK	COLOUR RENDERING /9	CONTROL GEAR /MDIM, /DALI, /BTC
----------------------	-------------------------------	---



Declaration of Conformity available