

DOWNLIGHTS / UNIVERSAL BEZEL / PHILIPS DLM


# Miro

Professional LED downlight with universal-bezel, emergency and wireless-control options.

Miro is listed as a professional high-performance LED downlight with minimalist die-cast bezel, Philips DLM LED module and driver system, and a 75 deg highly specular reflector.

The source file lists DALI, emergency and wireless control options, a universal bezel to accept decorative accessories, and project-variation options for connectors, cable, finish and performance.




 <p><b>Universal bezel</b> The source sheet lists /UB for decorative accessory compatibility.</p>	 <p><b>DALI and wireless</b> The source sheet lists /T+DALI and /BTC control options.</p>	 <p><b>Emergency options</b> Remote and integral indicator emergency options are listed.</p>	 <p><b>Over 60,000 hours</b> Nominal rated life is listed above 60,000 hours at L70/B10.</p>
--	--	---	---

## Key Features

- Professional high-performance LED downlight
- Universal bezel option to accept decorative accessories
- 75 deg highly specular reflector
- DALI, emergency and wireless control options
- Minimalist die-cast bezel in white RAL 9010
- Philips DLM LED module and driver system
- Nominal rated life above 60,000 hours at L70/B10

## Technical Drawing









<p>Cut-out <b>140 mm x 140 mm</b></p>	<p>Bezel <b>170 mm x 170 mm</b></p>
<p>Minimum ceiling thickness <b>5 mm</b></p>	<p>Maximum ceiling thickness <b>35 mm</b></p>
<p>Height <b>112 mm / 132 mm (60.5000 only)</b></p>	

## Ordering Information

OUTPUT (LLM)	COLOUR	POWER (TCW)	EFFICACY (LLM/TCW)	MODEL REF.
1075	3000K	9.5	113	<b>MIRO.1100.30</b>
1150	4000K	9.5	121	<b>MIRO.1100.40</b>
1850	3000K	17.5	106	<b>MIRO.2000.30</b>
2025	4000K	17.5	116	<b>MIRO.2000.40</b>
2850	3000K	30.0	95	<b>MIRO.3000.30</b>
3075	4000K	30.0	103	<b>MIRO.3000.40</b>
4425	3000K	46.0	96	<b>MIRO.5000.30</b>
4800	4000K	46.0	104	<b>MIRO.5000.40</b>

## Options

<p><b>BEZEL</b> /UB</p>	<p><b>CONTROL GEAR</b> /T+DALI, /BTC</p>	<p><b>EMERGENCY</b> /EM, /EMD, /EMS, /EMI, /EMDI, /EMSI</p>
-----------------------------	--	---

						Declaration of Conformity available
---	---	---	---	---	---	-------------------------------------

\*/LDC: We reserve the right to amend or change details without prior notification. E&UE.