

Aero

Compact commercial IP54 downlight with a low-glare reflector and selectable LED colour.



675 lm

STANDARD OUTPUT

9 W

STANDARD POWER


IP54

INGRESS PROTECTION

35.001

MODEL CODE

DIMENSIONS



LENGTH
110 mm

WIDTH
90 mm

HEIGHT
55 mm

LED COLOUR
3000 / 4000 /
5500 K

01 Output selection

ONE COMPACT OUTPUT WITH SELECTABLE LED COLOUR.

MODEL	OUTPUT	POWER	LED COLOUR	PROTECTION
35.001	675 lm	9 W	3000 / 4000 / 5500 K	IP54

Product output and dimensions are governed by the source data.

02 Configure Aero

CONTROL, EMERGENCY AND ACCESSORY OPTIONS ARE AVAILABLE FOR SELECTION.

AVAILABLE OPTION DETAILS					OUTPUT / CONTROL		EMERGENCY / ACCESSORY	
					/MDIM	Mains dimming	/EM	Emergency option
/MDIM Control	/ECO Control	/BTC Casambi	/EM Emergency	/EMD DALI	/ECO	Control option	/EMD	DALI emergency
					/BTC	Casambi control	BTWS001 / 002	Accessory options

PRODUCT VARIATIONS

/MDIM mains dimming - /ECO control - /BTC Casambi - /EM emergency - /EMD DALI emergency - BTWS001 / 002 accessories.

DOCUMENT

Technical data
REV 1

OPTICAL	PROTECTION	ELECTRICAL	FORMATS
Low-glare reflector with compact commercial format.	IP54 ingress protection for the selected installation.	9 W standard power with selectable LED colour.	110 × 90 × 55 mm product dimensions.