

Align

Fully adjustable single surface-mounted framelight for commercial interiors.



1025–3000 lm
STANDARD OUTPUT

9–31 W
STANDARD POWER

Up to 112.9 lm/W
SYSTEM EFFICACY

>60,000 h
L70 / F10 LIFE



LENGTH
225 mm

WIDTH
225 mm

HEIGHT
152 mm

REFLECTOR
Medium

01 Output selection

THREE OUTPUTS IN 3000 K AND 4000 K VERSIONS.

MODELS	OUTPUT	POWER	LED COLOUR	REFLECTOR
160.001 / .002	1025 lm	10 / 9 W	3000 / 4000 K	Medium
160.003 / .004	2000 lm	19 / 18 W	3000 / 4000 K	Medium
160.005 / .006	3000 lm	31 / 29 W	3000 / 4000 K	Medium

LED colour and electrical values vary by selected model.

02 Configure Align

REFLECTOR, CONTROL AND FINISH OPTIONS ARE AVAILABLE FOR SELECTION.

AVAILABLE OPTION DETAILS					OPTICAL / CONTROL		FINISH / PROJECT	
					/NB / /WB	Narrow or wide beam	/BK	Black finish
/NB Narrow beam	/WB Wide beam	/ECO Control	/R9 CRI	/BK Black	/ECO	Control option	/PV	Contact sales
					/R9	High R9 colour rendering	LED	3000 K or 4000 K

PRODUCT VARIATIONS

/NB narrow beam · /WB wide beam · /ECO control · /R9 colour rendering · /BK black finish · /PV contact sales.

DOCUMENT

Technical data
REV 1

OPTICAL	OUTPUT	CONSTRUCTION	FORMATS
Medium reflector standard; narrow and wide beam options.	1025 lm, 2000 lm and 3000 lm product outputs.	Adjustable surface-mounted framelight housing.	225 × 225 × 152 mm body dimensions.