

Axis

Miniature architectural LED downlight with compact 76 mm bezel, fixed or tilt formats and Tridonic SLA Essence light engine.



725–1,275 lm

LISTED OUTPUT RANGE

>50,000 h

L70/B50 MAINTENANCE

76 mm

COMPACT BEZEL

36°

STANDARD LED LENS

95 mm 001-3

75 mm 007-9

65 mm 004-6

67 mm cut-out

76 mm bezel

BEZEL

76 mm

CUT-OUT

67 mm

BODY DEPTH

65 / 75 / 90 mm

CEILING THICKNESS

26 mm max

01 Output selection

MODEL REF.	OUTPUT	COLOUR	POWER	SOURCE
AXIS.001	725 lm	2700 K	9.5 W	Tridonic SLA Essence
AXIS.002	775 lm	3000 K	9.5 W	
AXIS.003	825 lm	4000 K	9.5 W	
AXIS.004	775 lm	2700 K	10.5 W	
AXIS.005	850 lm	3000 K	10.5 W	
AXIS.006	900 lm	4000 K	10.5 W	
AXIS.007	1,150 lm	2700 K	14 W	
AXIS.008	1,175 lm	3000 K	14 W	
AXIS.009	1,275 lm	4000 K	14 W	

Output and power values are source data.

02 Specify Axis

CONTROL & EMERGENCY

/MDIM / /ECO /

Mains dimming, DALI / DSI, Casambi

/BTC

/EM / /EMD /

Emergency options

/EMM

BODY

/T

Tilt body

/BL / /BLT

Black or tilt black body

LENS & ACCESSORY

/SNB / /NB

12° or 24° lens

/HC

Honeycomb louvre

SPECIFICATION OPTIONS Control, emergency, body, lens and accessory choices for Axis.	DOCUMENT Technical data REV 1 / MAY 2026
--	---

ENGINE Tridonic SLA Essence platform.	LENS 36° LED lens as standard.	FINISH White RAL 9016 as standard.	MOUNTING Fixed or tilt ceiling arrangement.
---	--	--	---