

HighRack

Industrial LED high bay luminaire for warehouse aisles, high-rack storage and industrial halls.



8,025–11,850 lm

LISTED OUTPUT RANGE

70,000 h

L70 RATING

141 lm/tcW

MAXIMUM EFFICACY

4000 K

COLOUR TEMPERATURE

LENGTH

1719 mm

WIDTH

120 mm

BODY HEIGHT

69 mm

SUSPENSION OFFSET

180 mm

01 Output selection

TWO SOURCE-LISTED OUTPUT OPTIONS AT 4000 K.

MODEL REF.	OUTPUT	COLOUR	POWER	SOURCE
HIGHRACK.001	8,025 lm	4000 K	57 W	Philips LED and driver
HIGHRACK.002	11,850 lm	4000 K	88 W	Philips LED and driver

Output, power and system data are source data.

02 Specify HighRack

CONTROL, EMERGENCY, OPTIC AND ACCESSORY CHOICES ARE SOURCE-LISTED.

CONTROL & EMERGENCY

/T+DALI / /EA

Touch dimming or DALI; EasyAir sensor system

/EMI / /EMDI

Integral indicator or DALI / self-test emergency

OPTICS

/MB

Medium beam, 34°

/WB

Wide beam, 92°

ACCESSORIES

HIGHRACK.ACC.01

2 m suspension kit

HIGHRACK.ACC.02

EasyAir wall switch and app / APP

SPECIFICATION OPTIONS

Control, emergency, optic and accessory choices for HighRack schedules.

DOCUMENT

Technical data
REV 1 / MAY 2026

SYSTEM Philips LED and driver technology.	OPTICS Medium and wide beam choices.	CONTROL EasyAir sensor system option.	MOUNTING Surface, suspended or BESA mounting.
---	--	---	---