

Capsule

Adjustable LED track spot with 355° swivel and 320° tilt for focused architectural lighting.



3200-4675 lm
OUTPUT RANGE

27.0-41.5 W
POWER RANGE

355°
SWIVEL

320°
TILT

DIAMETER
Ø100 mm

HEIGHT
205 mm

REFLECTOR
40° standard

MOUNTING
Track



01 Output selection

SIX MODELS ACROSS THREE OUTPUTS AND TWO LED COLOURS.

MODEL	OUTPUT	POWER	LED COLOUR
80.001	3200 lm	27.0 W	3000K
80.002	3300 lm	27.0 W	4000K
80.003	4000 lm	35.0 W	3000K
80.004	4150 lm	35.0 W	4000K
80.005	4575 lm	41.5 W	3000K
80.006	4675 lm	41.5 W	4000K

3000K and 4000K models available across each listed output.

02 Configure Capsule

OPTICAL, FINISH AND TRACK-MOUNTED CONFIGURATION DETAILS.

AVAILABLE OPTION DETAILS


/ECO
ECO


/TOP
TOP


/NB
NB


/WB
WB


/BD
BD


/SN
SN


/WH
White body and
heatsink


/BK
Black body and
heatsink

Option codes

Option codes

Option codes

Option code

White / black body and heatsink

Global Trac / Stucchi / Eutrac

OUTPUT / OPTICAL

Option codes

Option codes

Option codes

FINISH / MOUNTING

Option code

White / black body and heatsink

Global Trac / Stucchi / Eutrac

PRODUCT VARIATIONS
/BKG / WH / BK / ECO / TOP / NB / WB / BD / SN / HC.

DOCUMENT
Technical data
REV 1

OPTICAL	MOVEMENT	FINISH	TRACK
40° reflector supplied as standard.	355° swivel with 320° tilt adjustment.	RAL 9016 white body with RAL 9007 grey heatsink.	Compatible with Global Trac, Stucchi and Eutrac.