

Crown

Compact surface-mounted LED downlight with an integral LED and driver system and low-glare multi-faceted reflector.



1,200-3,125 lm
ENGINE OUTPUT

9.5-24 W
SYSTEM POWER

3000K / 4000K
COLOUR TEMPERATURE

203 mm
BODY DIAMETER



MOUNTING
Surface mounted

DIAMETER
203 mm

CUT-OUT
Not required

FINISH
RAL9016 standard

01 Output selection

SIX OUTPUT AND COLOUR-TEMPERATURE CONFIGURATIONS ARE LISTED.

MODELS	OUTPUT	POWER	LED COLOUR	FINISH
15.001 / .002	1,200-1,250 lm	9.5 W	3000K / 4000K	RAL9016
15.003 / .004	1,900-2,000 lm	15 W	3000K / 4000K	RAL9016
15.005 / .006	2,950-3,125 lm	24 W	3000K / 4000K	RAL9016

Model-code, output and colour-temperature combinations follow the complete product data.

02 Configure Crown

CONTROL, EMERGENCY AND PERFORMANCE OPTIONS ARE AVAILABLE FOR SELECTION.

AVAILABLE OPTION DETAILS					CONTROLS	BODY OPTIONS
					/T+DALI TouchDIM / DALI control	/R9 High colour rendering
/T+DALI TouchDIM / DALI	/BTC Casambi wireless	/EMI Maintained emergency	/EMDI DALI emergency	/R9 High colour rendering	/BTC Casambi wireless control	/SA65 65 mm adaptor
					/EMI / /EMDI Maintained and DALI emergency	RAL9016 Brilliant white standard finish

PRODUCT VARIATIONS

/T+DALI TouchDIM / DALI · /BTC Casambi wireless · /EMI maintained emergency · /EMDI DALI emergency · /R9 high colour rendering · /SA65 65 mm adaptor.

DOCUMENT

Technical data
REV 3

OPTICAL	CONSTRUCTION	INSTALLATION	FINISH
Low-glare multi-faceted reflector.	Lightweight spun aluminium body.	Surface-mounted; no ceiling cut-out required.	RAL9016 brilliant white as standard.