

Dynamic

Professional high-performance LED downlight with a twist-and-lock bezel, satin reflector and configurable control and emergency arrangements.




1075-2825 lm
LUMINAIRE OUTPUT

10-26.5 W
LUMINAIRE POWER

>50,000 h
L80 / F10 LIFE

IP54 / IP65
PROTECTION OPTIONS



BODY HEIGHT
112 mm

CEILING DEPTH
5-40 mm max.

CUT-OUT
176 mm diameter

BEZEL
195 mm diameter

01 Output selection

FIVE STANDARD OUTPUT ENTRIES ARE LISTED AT 3,000K AND 4,000K; THE SOURCE SEPARATELY IDENTIFIES A TUNABLE-WHITE VARIANT.

MODEL	OUTPUT	POWER	LED COLOUR
110.2001	1150 lm	11 W	3,000K
110.2003	1075 lm	10 W	4,000K
110.2002	1900 lm	19.5 W	3,000K
110.2004	1875 lm	18 W	4,000K
110.3002 / .3004	2700-2825 lm	26.5 W	3,000K / 4,000K

110.2000/TUNE is listed separately at 1725 lm with 2,700-6,500K LED colour.

02 Configure Dynamic

REFLECTOR, CONTROL AND EMERGENCY ARRANGEMENTS.

REFLECTOR / EMERGENCY	CONTROLS / DRIVER	EMERGENCY / ACCESSORIES
 MF50 50 degree multi-facet  SP40 40 degree specular  ECO Control option  BTC Casambi Bluetooth  EMD DALI / self-test	/ECO SwitchDIM, DALI or DSI /BTC Casambi Bluetooth wireless network including dimming /65 IP65 option	EMERGENCY CODES /EM · /EMD · /EMS · /EMI · /EMDI · /EMSI REFLECTOR CODES /MF50 · /SP40 BEZEL CODE TA300/WH

PRODUCT VARIATIONS

TA300/WH bezel range · 60 degree satin etched reflector standard · /MF50 multi-facet and /SP40 specular reflector options · /ECO and /BTC control options · /65 IP65 option · /EM, /EMD, /EMS, /EMI, /EMDI and /EMSI emergency codes.

COMPLIANCE

UKCA · CE

OPTICAL CONTROL	SYSTEM	INTEGRATION	LIFE / PROTECTION
60 degree satin etched reflector supplied as standard; /MF50 and /SP40 options.	Tridonic-powered LED downlight with /ECO and /BTC control configurations.	Recessed body with 176 mm cut-out, 195 mm bezel and 5-40 mm max. recess.	>50,000 h L80/F10; IP54 / IP65 options.