

Edge-Lite

A slim edge-lit LED panel for recessed ceiling applications, with low-glare performance and configurable control, emergency and mounting accessories.




3400-4700 lm
LUMINAIRE OUTPUT

29-39 W
LUMINAIRE POWER

>50,000 h
L80 / B10 LIFE

UGR <19
LOW-GLARE RATING



PANEL WIDTH
595 mm

PANEL DEPTH
9 mm

FORMAT
595 × 595 mm

COLOUR
3000K / 4000K

01 Output selection

SIX MODEL REFERENCES ARE LISTED IN THE GOVERNING SOURCE TABLE.

OUTPUT	CCT	POWER	MODEL
3400 lm	3000K	29 W	20.001
3550 lm	4000K	29 W	20.002
4075 lm	3000K	35 W	20.003
4250 lm	4000K	35 W	20.004
4500 lm	3000K	39 W	20.005
4700 lm	4000K	39 W	20.006

02 Configure Edge-Lite

CONTROL, EMERGENCY AND MOUNTING ARRANGEMENTS.

SOURCE OPTION CROPS	CONTROLS / EMERGENCY	MOUNTING ACCESSORIES
 T+DALI Touch / DALI  MC MasterConnect  BTC Casambi wireless  EM 3hr emergency  EMS 3hr self-test	/T+DALI Touch dimming or DALI control driver /MC Philips MasterConnect wireless control driver /BTC Casambi wireless control driver /EM · /EMS 3hr emergency arrangements	SURF.178 Surface mounting accessory PBF.178 Plasterboard frame accessory SUS.178/1.2M Suspension accessory SAS001 Source-listed accessory

PRODUCT VARIATIONS
3000K / 4000K outputs, UGR <19 low-glare performance, wireless or wired control, emergency and mounting accessories as source-listed.

PERFORMANCE
Ra80 - L80/B10 >50,000 h

OPTICAL CONTROL Edge-lit panel with UGR <19 low-glare performance.	SYSTEM 29–39 W LED panel with source-listed control drivers.	INTEGRATION 595 × 595 mm panel format with 9 mm depth.	LIFE / COLOUR L80/B10 >50,000 hours; Ra80; 3000K or 4000K.
--	--	--	--