

Flexi

Professional adjustable LED downlight with a multi-faceted aluminium reflector, paired driver and options for control, emergency and high colour rendering.




1100-4975 lm
LUMINAIRE OUTPUT

8-40.5 W
LUMINAIRE POWER

L90 >66,000 h
LUMEN MAINTENANCE

5 years
WARRANTY



CUT-OUT
176 mm

BEZEL
186 mm

HEIGHT
102 mm

MAX. VOID
35 mm



01 Output selection

TEN STANDARD MODEL ENTRIES ARE GROUPED INTO FIVE PAIRED OUTPUT LEVELS.

MODELS	OUTPUT	POWER	LED COLOUR
79.001 - 79.002	1100-1125 lm	8.0 W	3,000K / 4,000K
79.003 - 79.004	1900-1950 lm	13.5 W	3,000K / 4,000K
79.005 - 79.006	2625-2700 lm	19.0 W	3,000K / 4,000K
79.007 - 79.008	3525-3625 lm	27.0 W	3,000K / 4,000K
79.009 - 79.010	4825-4975 lm	40.5 W	3,000K / 4,000K

The model pairs preserve the separate 830 and 840 entries in the governing source ordering table.

02 Configure Flexi

REFLECTOR, CONTROL, COLOUR RENDERING AND EMERGENCY ARRANGEMENTS.

REFLECTOR OPTIONS	CONTROLS / COLOUR	EMERGENCY / CONSTRUCTION
 /MF25 25 degree multi-faceted /MF60 60 degree multi-faceted /SP40 40 degree specular /SA50 50 degree satin etched	/T+DALI Touch dimming or DALI /BTC Casambi wireless network including dimming /R9 High colour rendering module	EMERGENCY /EM - /EMI - /EMD - /EMDI - /EMS - /EMSI REFLECTOR 40 degree multi-faceted reflector standard BUILD Designed for remanufacturing: white RAL 9010

PRODUCT VARIATIONS
Multi-faceted pure aluminium reflector - /MF25 - /MF60 - /SP40 - /SA50 - /R9 high colour rendering - /T+DALI and /BTC control - emergency variants.

DOCUMENT
Technical data
REV 1

OPTICAL CONTROL 40 degree pure aluminium reflector supplied as standard with alternative beam options.	SYSTEM Philips LED module and paired driver.	INTEGRATION 176 mm cut-out, 186 mm bezel, 102 mm height and 35 mm maximum void.	LIFE / OPTIONS L90 lumen maintenance over 66,000 hours; high CRI, DALI, wireless and emergency options.
--	--	---	---