

Fusion

A recessed LED downlight with a reduced-profile white bezel, satin etched reflector and Philips DLM LED and driver system.




1025-4550 lm
STANDARD OUTPUT

9.5-46.5 W
STANDARD POWER

>60,000 h
RATED LIFE L70/B10

IP54
LENS OPTION



CUT-OUT
176 mm

BEZEL
192 mm

HEIGHT
120 mm

MAX. VOID
35 mm

01 Output selection

STANDARD OUTPUT LEVELS PLUS THE 103.2000/TUNE TUNABLE-WHITE MODEL.

MODELS	OUTPUT	POWER	LED COLOUR
103.1100.30/40	1025-1100 lm	9.5 W	3,000K / 4,000K
103.2000.30/40	1750-1900 lm	17.5 W	3,000K / 4,000K
103.3000.30/40	2700-2925 lm	30.0 W	3,000K / 4,000K
103.5000.30/40	4200-4550 lm	46.5 W	3,000K / 4,000K
103.2000/TUNE	1925 lm	27.5 W	927-965 tunable white

Output, power and colour values are transcribed from the governing source table.

02 Configure Fusion

REFLECTOR, CONTROL, LENS AND EMERGENCY ARRANGEMENTS.

REFLECTOR OPTIONS  /MF50 59 degree multi-facet  /SP40 40 degree specular  /54 IP54 sealed lens  /T+DALI Touch dimming or DALI	CONTROLS / LENS /BTC Casambi wireless network including dimming /54 IP54 clear lens option /TUNE Tunable white option	EMERGENCY OPTIONS /EW / /EMD / /ENS Remote indicator variants /EMI / /EMDI / /ENSI Integral indicator variants NOTE Emergency options are not available with tunable white.
--	--	--

PRODUCT VARIATIONS
/MF50 · /SP40 · /54 sealed lens · /T+DALI · /BTC wireless control · emergency variants · tunable white.

DOCUMENT
Technical data
REV 1

OPTICAL CONTROL 60 degree satin etched reflector supplied as standard with multi-faceted and specular options.	SYSTEM Philips DLM LED module and driver system; Tridonic DLE tunable white option.	INTEGRATION 176 mm cut-out, 192 mm bezel, 120 mm height and 35 mm maximum void.	LIFE / OPTIONS Rated life over 60,000 hours at L70/B10 with IP54, wireless, dimming and emergency options.
--	---	---	--