

Glance

Low-glare adjustable scoop downlight for directional recessed lighting.




975–2625 lm
STANDARD OUTPUT

10–27 W
SYSTEM POWER

3000 / 4000 K
LED COLOUR

355° / 70°
SWIVEL / TILT



BEZEL
150 mm

CUT-OUT
140 mm

ABOVE CEILING
130 mm max

BELOW CEILING
105 mm max

01 Output selection

SIX MODEL REFERENCES ACROSS THREE OUTPUT AND POWER STEPS.

MODELS	OUTPUT	POWER	LED COLOUR	ADJUSTMENT
GLANCE.001 / .002	975–1050 lm	10 W	3000 / 4000 K	355° / 70°
GLANCE.003 / .004	1650–1775 lm	16 W	3000 / 4000 K	355° / 70°
GLANCE.005 / .006	2450–2625 lm	27 W	3000 / 4000 K	355° / 70°

Output, power and colour values are source data.

02 Configure Glance

REFLECTOR, CONTROL AND EMERGENCY SUFFIXES ARE AVAILABLE FOR SELECTION.

AVAILABLE OPTION DETAILS					REFLECTOR / CONTROL	EMERGENCY
					/NB 12 degree reflector /WB 40 degree reflector /T+DALI / /BTC Control options	/EM Emergency remote indicator /EMD DALI emergency remote indicator
/NB Narrow beam /WB Wide beam /T+DALI Control /BTC Casambi /EMD Emergency						

PRODUCT VARIATIONS

/NB narrow beam · /WB wide beam · /T+DALI touch dimming / DALI · /BTC Casambi · /EM emergency · /EMD DALI emergency.

DOCUMENT

Technical data
REV 1

BODY	REFLECTOR	LED	CONTROL
Adjustable die-cast scoop body.	24 degree standard reflector; 12 and 40 degree alternatives.	Premium white Ra90 LED module as standard.	Touch dimming, DALI and wireless control options.