

Glide

Four-foot LED batten with an aluminium body, integrated gear tray and opal diffuser for uniform general-lighting applications.



2925-5200 lm

LUMINAIRE OUTPUT

22.5-40 W

LUMINAIRE POWER

>125 lm/tcW

ETL EFFICACY

5 years

WARRANTY

3200 mm

1200 mm

55 mm

60 mm

15 mm

60 mm

CE

UKCA

RoHS

REACH

LENGTH

1200 mm

WIDTH

55 mm

HEIGHT

60 mm

LIFE

>50,000 h

01 Output selection

FOUR 4,000K STANDARD OUTPUTS WITH CLOSELY MATCHED SYSTEM EFFICACY.

MODEL	OUTPUT	POWER	LED COLOUR	EFFICACY
177.001	2925 lm	22.5 W	840	130 lm/tcW
177.002	3675 lm	28.5 W	840	129 lm/tcW
177.003	4450 lm	34 W	840	131 lm/tcW
177.004	5200 lm	40 W	840	130 lm/tcW

Outputs, power and efficacy are transcribed from the governing source ordering table.

02 Configure Glide

CONTROL, EMERGENCY AND CONNECTED SENSOR ARRANGEMENTS.

SOURCE OPTION DETAILS

SwitchDIM

DALI

DSI

/ECO

SwitchDIM / DALI / DSI

/EMI

Integral emergency

/EMDI

DALI / self-test

CONTROLS

/ECO

SwitchDIM, DALI or DSI

/PV

Presence sensor variants

WIRELESS

HubSense or Casambi

CONSTRUCTION

BODY

Aluminium with integral gear tray

DIFFUSER

Opal, homogeneous output

ENTRY

BESA points and 20 mm conduit

PRODUCT VARIATIONS

/ECO control · /EMI integral emergency · /EMDI DALI or self-test emergency · presence sensor, HubSense and Casambi variants.

DOCUMENT

Technical data
REV 1

OPTICAL

Opal diffuser provides homogeneous output.

SYSTEM

Tridonic-powered LED platform.

INSTALLATION

1200 x 55 x 60 mm with BESA fixing points.

LIFE / SUPPORT

L70/B50 beyond 50,000 hours; five-year warranty.

LUMENLOOP

Figures and options are taken from the governing source PDF. Details may change without notice. E&OE.

02045 721 554
INFO@LUMENLOOP.CO.UK
LUMENLOOP.CO.UK