

Harbor

A contemporary surface-mounted LED bulkhead with a high-transmission opal diffuser, concealed-fixing bezel and IP65 / IK10 construction.



1200-2350 lm

LUMINAIRE OUTPUT

10-21 W

LUMINAIRE POWER

72,000 h

L80 LIFE

IP65 / IK10

PROTECTION

DIAMETER

380 mm

PROFILE

122 mm

MOUNTING

Surface

IMPACT RATING

IK10

122 mm

ø380 mm

ø380 mm

CE

UKCA

RoHS

01 Output selection

THREE OUTPUT FAMILIES WITH 830 OR 840 LED COLOUR OPTIONS.

MODELS	OUTPUT RANGE	POWER	LED COLOUR	FORMAT
167.001 / .002	1200-1250 lm	10 W	830 / 840	Low output
167.003 / .004	1600-1700 lm	14 W	830 / 840	Standard
167.005 / .006	2225-2350 lm	21 W	830 / 840	High output

For individual ordering and compatibility, refer to the complete product data.

02 Configure Harbor

FINISH, CONTROL, EMERGENCY AND SENSOR OPTIONS AVAILABLE FOR SELECTION.

AVAILABLE OPTION DETAILS

/BL
Black bezel

/ECO
SwitchDIM / DALI / DSI

/EMDI
Integral emergency indicator

/HALO
Back-lit halo

/AT
Anti-tamper screws

CONTROL / EMERGENCY

/ECO

SwitchDIM, DALI or DSI

/BTC

Casambi Bluetooth

/EMI / /EMDI

Integral emergency

CONSTRUCTION / SENSING

/BL

Black bezel finish

/HALO

Back-lit halo effect

/AT

Anti-tamper screws

PRODUCT VARIATIONS

/BL black bezel · /ECO · /BTC · remote and integral emergency · /AT anti-tamper · /HALO back-lit halo · sensor options available.

DOCUMENT

Technical data
REV 2

OPTICAL High-transmission opal diffuser for even circular illumination.	CONSTRUCTION Concealed-fixing surface bezel with 380 mm diameter.	PROTECTION IP65 ingress protection and IK10 impact resistance.	FORMATS 1200-2350 lm across three output families.
---	---	--	--