

Line

Continuous direct profile with through-wiring and a mechanical joining kit supplied with every product.




1725-5425 lm
STANDARD OUTPUT

18-50 W
STANDARD POWER

>72,000 h
L80 / F10 LIFE

RAL 9006
STANDARD FINISH



WIDTH
72 mm

HEIGHT
62 mm

LENGTHS
850 mm-2.5 m

MOUNTING
**Surface /
suspension**

01 Output selection

EIGHT MODELS ACROSS FOUR LENGTHS AND TWO LED COLOUR CODES.

MODELS	LENGTH	OUTPUT	POWER	LED COLOUR
173.001 / .002	850 mm	1725-1825 lm	18 W	830 / 840
173.003 / .004	1.2 m	2575-2725 lm	25 W	830 / 840
173.005 / .006	1.5 m	3150-3325 lm	31 W	830 / 840
173.007 / .008	2.5 m	5150-5425 lm	50 W	830 / 840

Higher-output variants extend the range to 8575 lm; refer to the complete product data for ordering.

02 Configure Line

PROFILE, OUTPUT, LENS, CONTROL AND MOUNTING OPTIONS AVAILABLE FOR SELECTION.

AVAILABLE OPTION DETAILS					OUTPUT / CONTROL		FINISH / MOUNTING	
					/LO / /HO	Lower or higher output	/WH / /BK	White or black body
/SE Start / end section					/LG	Low glare prismatic lens	/EMI	Integral emergency
/WH white body					/ECO	SwitchDIM, DALI or DSI	/SUS	Suspension kit
/BK black body								
/LO lower output								
/LG low glare lens								

PRODUCT VARIATIONS

/SE start/end · /WH white · /BK black · /LO / /HO output · /LG low glare · /ECO · /EMI · /SUS suspension.

DOCUMENT

Technical data
REV 3

OPTICAL

TPa opal lens standard; low-glare prismatic lens option available.

CONSTRUCTION

Continuous extruded linear profile with mechanical joining kit.

FINISH

RAL 9006 standard with white or black body options.

FORMATS

850 mm, 1.2 m, 1.5 m and 2.5 m modules.