

Luma

Ultra-low-glare LED linear luminaire with deep dark-light baffles, a low-profile body and controlled office optics.



1850–4675 lm

LUMINAIRE OUTPUT

14–33 tcW


POWER RANGE

UGR 12–14

BY LISTED MODEL

>75,000 h

L80 / F10



OFFICIAL DIMENSIONAL DRAWING

NOT TO SCALE

LENGTH
1271 / 1550 mm

SECTION
62 × 72 mm

FORMATS
1.2 / 1.5 m

MOUNTING
Surface /
suspended

Luma
Designed and made in the UK

01 Ordering information

STANDARD 50° CONTROLLED OFFICE LENS. LO AND HO DENOTE LOWER- AND HIGHER-OUTPUT VARIANTS.

MODEL	LENGTH	CCT	OUTPUT	POWER	UGR	EFFICACY
LUMA.001/LO	1.2 m	3000K	1850 lm	14 tcW	12	132 llm/tcW
LUMA.001	1.2 m	3000K	2725 lm	20 tcW	13	136 llm/tcW
LUMA.001/HO	1.2 m	3000K	3575 lm	27 tcW	14	132 llm/tcW
LUMA.002/LO	1.2 m	4000K	1925 lm	14 tcW	12	138 llm/tcW
LUMA.002	1.2 m	4000K	2850 lm	20 tcW	13	143 llm/tcW
LUMA.002/HO	1.2 m	4000K	3750 lm	27 tcW	14	139 llm/tcW
LUMA.003/LO	1.5 m	3000K	2300 lm	17 tcW	12	135 llm/tcW
LUMA.003	1.5 m	3000K	3425 lm	25 tcW	13	137 llm/tcW
LUMA.003/HO	1.5 m	3000K	4475 lm	33 tcW	14	136 llm/tcW
LUMA.004/LO	1.5 m	4000K	2400 lm	17 tcW	12	141 llm/tcW
LUMA.004	1.5 m	4000K	3575 lm	25 tcW	13	143 llm/tcW
LUMA.004/HO	1.5 m	4000K	4675 lm	33 tcW	14	142 llm/tcW

02 Configure Luma

TRIDONIC LED AND DRIVER PLATFORM.

FINISH / BAFFLE	OPTICS / CONTROLS	EMERGENCY / ACCESSORIES
 Grey RAL 9006  White /WH RAL 9016  Black /BK RAL 9005  Dark-light Standard  Soft-light /WSB	50° Standard controlled office lens /WB 80° wide beam lens /ECO SwitchDIM, DALI or DSI /BTC Bluetooth control inc. dimming	/EMI Emergency integral indicator /EMSI Self-test emergency integral indicator /ENDI DALI emergency integral indicator ACC.01-04 Joining, suspension and baffle tool

PRODUCT VARIATIONS
Multiple baffle segments · direct/indirect · high CRI · asymmetric wall-wash baffles · gloss black, chrome-effect or matt silver baffles · tunable white · integral sensors · higher output · 35° medium, 25 × 70° oval or 80° batwing lenses.

COMPLIANCE
UKCA · CE · DC Declaration of Conformity available.

OPTICAL CONTROL Premium matt black dark-light baffles and 50° office lens as standard.	SYSTEM Tridonic LED and driver platform with SwitchDIM, DALI or DSI control options.	MOUNTING Surface mounted as standard, with suspension kit available.	BODY FINISH RAL 9006 grey as standard; RAL 9016 white or RAL 9005 black options.
--	--	--	--