

Lumi

Low-profile IP54 downlight with a recessed opal diffuser for architectural commercial interiors.




1475–3500 lm
LUMINAIRE OUTPUT

13–31.5 W
LUMINAIRE POWER

3000 / 4000 / 5600 K
LED COLOUR

IP54
INGRESS PROTECTION



228 mm
BEZEL

200 mm
CUT-OUT

45 mm
DEPTH

LUMI.001 to .004
MODELS

01 Output selection

FOUR MODEL REFERENCES ACROSS THE SWITCHABLE CCT PLATFORM.

MODEL	OUTPUT	POWER	LED COLOUR	EFFICACY
LUMI.001	1475–1625 lm	13–13.5 W	3000 / 4000 / 5600 K	109–125 lm/tcW
LUMI.002	2025–2275 lm	18.5–19.5 W	3000 / 4000 / 5600 K	107–123 lm/tcW
LUMI.003	2350–2700 lm	22–23 W	3000 / 4000 / 5600 K	102–123 lm/tcW
LUMI.004	3025–3500 lm	30–31.5 W	3000 / 4000 / 5600 K	96–117 lm/tcW

Output, power and efficacy values are source data.

02 Configure Lumi

CONTROL AND EMERGENCY SUFFIXES ARE AVAILABLE FOR SELECTION.

AVAILABLE OPTION DETAILS



/MDIM
Mains dim



/ECO
Control



/BTC
Casambi



/EM
Emergency



/EMD
DALI

CONTROL GEAR

/MDIM Phase-cut mains dimming

/ECO SwitchDIM / DALI / DSI

/BTC Casambi wireless control

EMERGENCY

/EM Emergency remote indicator

/EMD DALI / self-test emergency remote indicator

PRODUCT VARIATIONS
/MDIM phase-cut dimming · /ECO SwitchDIM / DALI / DSI · /BTC Casambi · /EM emergency · /EMD DALI / self-test emergency.

DOCUMENT
Technical data
REV 1

DIFFUSER Recessed opal PC diffuser.	BEZEL White RAL 9016 bezel.	LED SMD LED engine powered by Tridonic.	LIFE 50,000 hours L70 stated in source features.
---	---------------------------------------	---	--