

Natura

Back-lit IP54 LED light box with an ultra-thin square bezel.



700–2225 lm
STANDARD OUTPUT

7.0–20.5 W
SYSTEM POWER

3000 / 4000 K
LED COLOUR

IP54
INGRESS PROTECTION



BEZEL
244 × 244 mm

CUT-OUT
220 × 220 mm

ABOVE CEILING
82 mm

CEILING RECESS
35 mm max

01 Output selection

MODELS	OUTPUT	POWER	LED COLOUR	EFFICIENCY
NATURA.001 / .002	700–725 lm	7 W	3000 / 4000 K	100–104 lm/tcW
NATURA.003 / .004	1125–1175 lm	10.5 W	3000 / 4000 K	107–112 lm/tcW
NATURA.005 / .006	1525–1600 lm	14 W	3000 / 4000 K	109–114 lm/tcW
NATURA.007 / .008	2100–2225 lm	20.5 W	3000 / 4000 K	102–109 lm/tcW

Output, power, colour and efficiency values are source data.

02 Configure Natura

AVAILABLE OPTION DETAILS	CONTROL	EMERGENCY
SwitchDIM DALI DSI /ECO Control CASAMBI /BTC Casambi /EM Emergency /EMD Emergency /EMM Mesh EM	/ECO SwitchDIM, DALI & DSI /BTC Casambi wireless network	/EM Emergency remote indicator /END / /EMM DALI / wireless mesh emergency

PRODUCT VARIATIONS

/ECO SwitchDIM, DALI & DSI - /BTC Casambi - /EM emergency - /EMD DALI emergency - /EMM wireless mesh emergency.

DOCUMENT

Technical data
REV 1

BODY	BEZEL	LED	PROTECTION
Back-lit square light-box construction.	Ultra-thin square bezel.	3000 K and 4000 K source options.	IP54 rated construction.