

Opti

Square recessed LED downlight with high-specular optics and decorative bezel accessories.




1200–3025 lm
FIXED OUTPUT

10–26 W
SYSTEM POWER

3000 / 4000 K
LED COLOUR

118.1 lm/W
MAXIMUM EFFICACY



BEZEL
170 × 170 mm

CUT-OUT
140 × 140 mm

BODY DEPTH
112 mm

CEILING THICKNESS
5–35 mm

01 Output selection

FIXED WHITE AND TUNABLE-WHITE MODEL REFERENCES.

MODELS	OUTPUT	POWER	LED COLOUR	CONFIGURATION
OPTI.001 / .003	1200 lm	11 / 10 W	3000 / 4000 K	Fixed white
OPTI.002 / .004	2075 / 3025 lm	19 / 18 / 26 W	3000 / 4000 K	Fixed white
OPTI.000	1725 lm	18 W	2700–6500 K	Tunable white

Output, power, colour and configuration values are source data.

02 Configure Opti

CONTROL, EMERGENCY AND DECORATIVE BEZEL SUFFIXES ARE AVAILABLE FOR SELECTION.

AVAILABLE OPTION DETAILS



/ECO
Control



/BTC
Casambi



/EM
Emergency



/EMD
Emergency



/DA001
Bezel

CONTROL

/ECO SwitchDIM, DALI & DSI

/BTC Casambi wireless network

/UB U-bracket option

EMERGENCY / BEZEL

/EM / /EMD Emergency options

/DA001–/DA004 Decorative bezel accessories

PRODUCT VARIATIONS

/ECO control · /BTC Casambi · /EM emergency · /EMD DALI emergency · /EMI /EMDI emergency variants · /UB U-bracket · /DA001–/DA004 decorative bezels.

DOCUMENT

Technical data
REV 1

OPTICS High-specular optical system.	LED Fixed white and tunable-white configurations.	BEZEL Decorative bezel accessories available.	CONTROL Control and emergency suffixes available.
--	---	---	---