

Optima

Surface-mounted LED downlight with Philips technology, suspension options and a broad accessory set.



1200–3800 lm
STANDARD OUTPUT

14.0–46.5 W
SYSTEM POWER

3000 / 4000 K
LED COLOUR

60,000 h
L70 / B10



HEIGHT
238 mm

DIAMETER
200 mm

MOUNTING
Surface / pendant

REFLECTOR
60° standard

01 Output selection

EIGHT MODEL REFERENCES ACROSS FOUR OUTPUT AND POWER STEPS.

MODELS	OUTPUT	POWER	LED COLOUR	OPTIC
OPTIMA.001 / .002	1200–1300 lm	14 W	3000 / 4000 K	60° standard
OPTIMA.003 / .004	1900–2075 lm	24 W	3000 / 4000 K	50° / 40° optional
OPTIMA.005 / .006	2550–2775 lm	34.5–35 W	3000 / 4000 K	50° / 40° optional
OPTIMA.007 / .008	3475–3800 lm	46.5 W	3000 / 4000 K	50° / 40° optional

Output, power, colour and optic values are source data.

02 Configure Optima

CONTROL, SUSPENSION AND GLASS ACCESSORY CODES ARE AVAILABLE FOR SELECTION.

AVAILABLE OPTION DETAILS				CONTROL / SUSPENSION		GLASS ACCESSORIES	
				/T+DALI Touch dimming / DALI		TA340–TA344 Clear, etched and polycarbonate glass	
/T+DALI Control				/SUSW / /SUSG / /SUSB 2 m suspension kits		/MF50 / /SP40 50° multi-faceted / 40° specular	
/SUSW Suspension							
TA340 Glass							
TA341 Glass							

PRODUCT VARIATIONS

/T+DALI control · /SUSW, /SUSG, /SUSB suspension · TA340–TA344 glass · /MF50 and /SP40 reflector options.

DOCUMENT

Technical data
REV 1

BODY	LED	REFLECTOR	MOUNTING
Spun aluminium surface downlight.	Philips LED and driver system.	60° satin etched reflector standard.	Surface or 2 m suspended option.