

Prisma

Track-mounted LED spotlight with Philips Premium White Ra90 LED and adjustable optical control.



1150–3725 lm

STANDARD OUTPUT

11.5–43.5 W

SYSTEM POWER

3000 / 4000 K

LED COLOUR

Ra90

PHILIPS PREMIUM WHITE

Dimensions

PRODUCT DRAWING

BODY

130 mm

DEPTH

70 mm

DIAMETER

Ø100 mm

HEIGHT

205 mm

01 Output selection

MODELS	OUTPUT	POWER	LED COLOUR	ADJUSTMENT
PRISMA.001 / .002	1150–1250 lm	11.5 W	3000 / 4000 K	355° / 320°
PRISMA.003 / .004	1800–1925 lm	19.5 W	3000 / 4000 K	355° / 320°
PRISMA.005 / .006	2425–2600 lm	27 W	3000 / 4000 K	355° / 320°
PRISMA.007 / .008	3450–3725 lm	43.5 W	3000 / 4000 K	355° / 320°

Output, power, colour and adjustment values are source data.

02 Configure Prisma

AVAILABLE OPTION DETAILS

/NB

25° beam

/WB

60° beam

/BD

Barn doors

/DALI

Control

BEAM / ACCESSORIES

/NB / /WB

25° narrow / 60° wide beam

/BD / /SN / /HC

Barn doors / snoot / honeycomb

TRACK / CONTROL

GLOBAL / STUCCHI / EUTRAC

Track systems

/DALI

DALI control

PRODUCT VARIATIONS

/NB and /WB beams · /BD, /SN and /HC accessories · /DALI control · Global, Stucchi and Eutrao track.

DOCUMENT

Technical data
REV 1

LED Philips Premium White Ra90 LED.	OPTIC 40° low-glare optic standard.	AIM 355° swivel / 320° tilt.	MOUNTING Track-mounted spotlight.
---	---	--	---

LUMENLOOP

Figures and options are provided for product selection. Details may change without notice. E60E.

02045 721 554
INFO@LUMENLOOP.CO.UK
LUMENLOOP.CO.UK