

Protec

Compact fire-rated IP65 LED downlight with a multi-faceted reflector, protected ceiling gasket and clean bezel options.



750–775 lm
LISTED OUTPUT

8 tcW
LISTED POWER

3000 / 4000 K
LED COLOUR

IP65
INGRESS PROTECTION

BEZEL
85 mm

CUT-OUT
73 mm

DEPTH
60 mm

FIRE RATING
FR30 / FR60 / FR90

01 Output selection

TWO SOURCE-LISTED SELECTIONS ACROSS TWO LED COLOURS.

OUTPUT	POWER	LED COLOUR	INGRESS	SELECTION
750 lm	8 tcW	3000 K	IP65	Source-listed
775 lm	8 tcW	4000 K	IP65	Source-listed

Output and power values are source data.

02 Configure Protec

BEZEL, CONTROL AND EMERGENCY CHOICES ARE SOURCE-LISTED.

AVAILABLE OPTION DETAILS


Brushed Bezel


Black Bezel


/MDIM Control


/ECO Control


/BTC Control


/EM Emergency


/EMD Emergency

BEZEL / CONTROL

BEZEL

White standard; brushed aluminium or black options

/MDIM

Phase-cut mains dimming

/ECO

SwitchDIM / DALI / DSI

/BTC

Casambi wireless network including dimming

EMERGENCY

/EM

3 hour emergency conversion*

/EMD

3 hour self-test and DALI emergency conversion*

PRODUCT VARIATIONS
Bezel, control and emergency choices.

DOCUMENT
Technical data
REV 1

FIRE RATED Accredited FR30, FR60 and FR90 coverage.	RATED LIFE 40,000 hours L70 / F50.	REFLECTOR Multi-faceted reflector for a controlled recessed appearance.	EMERGENCY *Remote indicators and ILEMs are not IP65 or fire rated.
---	--	---	--