

Safe Emergency

Track-mounted emergency module with LiFePO4 batteries, three-hour non-maintained operation and source-listed self-test or DALI emergency options.



254 lm

EMERGENCY OUTPUT

2.5 W

SYSTEM POWER

3 hour

NON-MAINTAINED OPERATION

LiFePO4

BATTERY

LENGTH

330 mm

DEPTH

50 mm

HEIGHT

83 mm

TRACK

3 adaptor families

01 Product selection

ONE SOURCE-LISTED TRACK-MOUNTED EMERGENCY CONFIGURATION.

PRODUCT	FORMAT	OUTPUT	POWER	OPERATION
Track-mounted emergency module		254 lm	2.5 W	3 hour non-maintained

Output and power values are source data.

02 Specify Safe Emergency

CONFIRM THE REQUIRED TRACK ADAPTOR, EMERGENCY OPTION AND FINISH.

TRACK ADAPTOR	EMERGENCY OPTION	FINISH
GLOBAL TRAC Source-listed compatibility	/EMD DALI emergency option	WHITE Standard finish
STUCCHI Source-listed compatibility	SELF-TEST Source-listed emergency option	/BK Black finish option
EUTRAC Source-listed compatibility		

PRODUCT VARIATIONS

Three track adaptor families, DALI or self-test emergency option, white standard or black finish.

DOCUMENT

Technical data
REV 1

OUTPUT 254 lm emergency output.	OPERATION Three-hour non-maintained operation.	BATTERY Long-life LiFePO4 battery.	MOUNTING Track-mounted module.
---	--	--	--