

Shaper Track

FramiFlex track-mounted framing projector with four adjustable aperture plates, focus and zoom dampening adjustment.



525–975 lm
LISTED OUTPUT RANGE

Four plates
ADJUSTABLE APERTURES

Focus / zoom
DAMPENING ADJUSTMENT

L90 / 55,000 h
LISTED MAINTENANCE

LENGTH
158–250 mm

DIAMETER
Ø64 mm

BODY
130 mm

ROTATION
90°

01 Output selection

EIGHT SOURCE-LISTED OUTPUT OPTIONS IN 3000 K AND 4000 K.

MODEL / COLOUR	OUTPUT	POWER	PRODUCT EFFICACY
SHAPERTRACK.001/LO / 3000 K	525 lm	11.0 tcW	Not listed
SHAPERTRACK.002/LO / 4000 K	525 lm	11.0 tcW	Not listed
SHAPERTRACK.001 / 3000 K	625 lm	14.0 tcW	Not listed
SHAPERTRACK.002 / 4000 K	650 lm	14.0 tcW	Not listed
SHAPERTRACK.003 / 3000 K	800 lm	20.5 tcW	Not listed
SHAPERTRACK.004 / 4000 K	825 lm	20.5 tcW	Not listed
SHAPERTRACK.005 / 3000 K	950 lm	26.5 tcW	Not listed
SHAPERTRACK.006 / 4000 K	975 lm	26.5 tcW	Not listed

Output and power values are source data; product efficacy is not listed in the governed sheet.

02 Specify Shaper Track

FINISH, COLOUR-RENDERING AND CONTROL CHOICES ARE SOURCE-LISTED.

FINISH / COLOUR

WHITE

Standard finish

/BK

Black finish

/9

Ra90 option

CONTROLS

/MDIM

Mains dimming

/DALI

DALI control gear

/BTC

Wireless control

FRAMING

FOUR PLATES

Adjustable aperture framing

FOCUS / ZOOM

Dampening adjustment

SPECIFICATION OPTIONS
Finish, colour rendering, controls and framing adjustment.

DOCUMENT
Technical data
REV 1 / JUNE 2026

FRAMIFLEX
LED shape shifter lens.

FRAMING
Portrait, landscape, blade and irregular designations.

SYSTEM
Vossloh LED and in-track driver system.

COLOUR
Ra90 option.