

Solace

Extruded aluminium circular pendant with opal acrylic diffuser, 1.4 m suspension and 600 mm or 1200 mm diameters.



2,625–5,025 lm

LISTED OUTPUT RANGE

50,000 h

L70 LIFE

600 / 1200 mm

LISTED DIAMETERS

1.4 m

MAXIMUM SUSPENSION

600 MM VARIANT

Ø600 × 105 mm

1200 MM VARIANT

Ø1200 × 105 mm

SUSPENSION

1.4 m max

DIFFUSER

Opal acrylic

105 mm

1.4 m max

600 / 1200 mm

01 Output selection

TWO SOURCE-LISTED MODEL REFERENCES AT 4000 K.				
MODEL REF.	OUTPUT	COLOUR	POWER	EFFICACY
SOLACE.001	2,625 lm	4000 K	47 W	56 lm/tcW
SOLACE.002	5,025 lm	4000 K	83 W	60 lm/tcW

Output, power and efficacy values are source data.

02 Specify Solace

CONTROL GEAR

/T+DALI / /DALI Dimming and DALI options

FINISH

/BK / /GY Black or grey finish options

PROJECT VARIATIONS

ANY RAL Any RAL colour

UPLIGHT Additional uplight

SPECIFICATION OPTIONS

Control, finish and product variation choices for Solace.

DOCUMENT

Technical data
REV 1 / JUNE 2026

BODY

High-quality extruded aluminium.

DIFFUSER

Opal acrylic for homogeneous illumination.

LIFE

50,000 hours at L70.

ORIGIN

Made in the UK marking.