

Stucchi OneTrack

Surface-mounted track system based on the Eurostandard Plus platform, suitable for use with Global Trac adaptors.



1 m / 2 m SOURCE-LISTED LENGTHS	3 circuit TRACK SYSTEM	37.8 mm TRACK WIDTH	DALI COMPATIBILITY
		37.8 mm WIDTH	31.4 mm HEIGHT
		Black / white FINISH	2 m wire kit SUSPENSION

01 Track and accessory selection

SOURCE-LISTED WHITE AND BLACK COMPONENTS FOR MODULAR LAYOUTS.

DESCRIPTION	WHITE	BLACK	FORMAT
1 m track	9000A-1/W-ST	9000A-1/B-ST	Surface
2 m track	9000A-2/W-ST	9000A-2/B-ST	Surface
End feed	9001/W	9001/B	Feed
Straight connector	9003/W	9003/B	Connector
L-connector / feed	9011/W	9011/B	Connector

Further source-listed components: end cap 9004/W or 9004/B; flexible adjustable corner connector 9018/W or 9018/B.

02 Specify OneTrack

CORE SYSTEM COMPATIBILITY AND ACCESSORY REFERENCES ARE SOURCE-LISTED.

SYSTEM BASIS PLATFORM Eurostandard Plus ADAPTORS Suitable for Global Trac adaptors	SUSPENSION S-9000/T Accessory tool SUS.TRK/2M 2 m wire suspension kit	TRACK ACCESSORIES 9001 / 9003 Feed and straight connector 9004 / 9011 / 9018 End cap and corner accessories
---	--	--

SPECIFICATION OPTIONS

Track lengths, feeds, connectors, finish and suspension arrangements.

DOCUMENT

Technical data
REV 1 / JUNE 2026

SYSTEM Surface-mounted lighting track system.	PLATFORM Based on the Eurostandard Plus platform.	COMPATIBILITY Three circuit and DALI compatible.	FINISH Available in black or white.
---	---	--	---