

# Summit

Professional surface-mounted LED downlight with integral Tridonic LED and driver system, a brilliant white finish as standard and a low-glare multi-faceted reflector.



1,175–3,125 lm  
LISTED OUTPUT RANGE

203 mm  
DIAMETER

136 lm/tcW  
MAXIMUM EFFICACY

>60,000 h  
L80/B10  
RATED LIFE



DIAMETER  
203 mm

HEIGHT  
165 mm

MOUNTING  
Surface-mounted

REFLECTOR  
Low-glare multi-faceted

## 01 Output selection

SIX SOURCE-LISTED OUTPUT OPTIONS IN 3000 K AND 4000 K.

| MODEL / COLOUR      | OUTPUT   | POWER    | PRODUCT EFFICACY |
|---------------------|----------|----------|------------------|
| SUMMIT.001 / 3000 K | 1,175 lm | 9.5 tcW  | 126 lm/tcW       |
| SUMMIT.002 / 4000 K | 1,250 lm | 9.5 tcW  | 132 lm/tcW       |
| SUMMIT.003 / 3000 K | 1,875 lm | 14.5 tcW | 129 lm/tcW       |
| SUMMIT.004 / 4000 K | 1,975 lm | 14.5 tcW | 136 lm/tcW       |
| SUMMIT.005 / 3000 K | 2,975 lm | 23.0 tcW | 129 lm/tcW       |
| SUMMIT.006 / 4000 K | 3,125 lm | 23.0 tcW | 136 lm/tcW       |

Output, power and efficacy values are source data.

## 02 Specify Summit

FINISH, REFLECTOR, CONTROL, EMERGENCY AND SUSPENSION CHOICES ARE SOURCE-LISTED.

| FINISH / REFLECTOR             | CONTROLS                      | EMERGENCY / SUSPENSION                  |
|--------------------------------|-------------------------------|-----------------------------------------|
| /BK / /GY / /WH Finish options | /ECO Control gear             | /EMI / /EMDI Integral emergency options |
| /SA65 Satin etched reflector   | /BTC Casambi wireless network | /SUS / /SUS.B Suspension kits           |
| /R9 Premium White LED          |                               |                                         |

### SPECIFICATION OPTIONS

Finish, reflector, control, emergency and suspension choices.

### DOCUMENT

Technical data  
REV 1 / JUNE 2026

| OPTICS                                         | COLOUR                           | SYSTEM                                   | FINISH                               |
|------------------------------------------------|----------------------------------|------------------------------------------|--------------------------------------|
| Low-glare multi-faceted reflector as standard. | MacAdam colour tolerance 3 SDCM. | Integral Tridonic LED and driver system. | Brilliant white RAL9016 as standard. |