

Titan

Robust circular LED bulkhead for practical industrial and commercial interiors.



IP54 INGRESS RATING	IK10 IMPACT RATING	2,700 lm DELIVERED OUTPUT	50,000 h L70/B50 LIFE RATING
 A technical diagram showing the dimensions of the Titan LED bulkhead. It is a circular fixture with a diameter of 300 mm and a depth of 58 mm.		DIAMETER 300 mm	DEPTH 58 mm
		POWER 25 tcW	DISTRIBUTION 180°

01 Output selection

ONE SOURCE-LISTED CONFIGURATION WITH SWITCHABLE 3000 K, 4000 K AND 5500 K COLOUR TEMPERATURE.

MODEL REF.	OUTPUT	POWER	COLOUR TEMPERATURE	MOUNTING
TITAN.001	2,700 lm	25 tcW	3000 K / 4000 K / 5500 K	Ceiling or wall

The model reference covers the listed delivered output, power and switchable colour temperature configuration.

02 Specify Titan

CORE CONSTRUCTION AND INSTALLATION INFORMATION IS GOVERNED BY THE TECHNICAL DATA.

CONSTRUCTION	OPTIC & ENGINE	INSTALLATION
IP54 Practical internal use	TP (A) Opal polycarbonate diffuser	180° Broad light distribution
IK10 Higher-impact locations	SMD LED Integral driver platform	WALL / CEILING Surface-mounted installation

SPECIFICATION GUIDANCE

For emergency or sensor requirements, use the Sentinel or Harbor bulkhead ranges.

DOCUMENT

Technical data
REV 2 / MAY 2026

FORM Circular 300 mm bulkhead.	DIFFUSER Opal TP(a) polycarbonate.	COLOUR Switchable 3000 K / 4000 K / 5500 K.	MOUNTING Wall or ceiling mounted.
--	--	---	---