

# Uni-Fit

Curved IP44 LED linear luminaire for education, healthcare and practical refurbishment projects.



**3675–5275 lm**

STANDARD OUTPUT

**1200 / 1500 mm**

LISTED LENGTHS

**3000 / 4000 K**

LED COLOUR

**>50,000 h**

L70 / B50



WIDTH

**207 mm**

HEIGHT

**80 mm**

LENGTHS

**1200 / 1500 mm**

INGRESS

**IP44**

## 01 Output selection

FOUR MODEL REFERENCES ACROSS TWO LENGTHS AND COLOUR TEMPERATURES.

| MODEL      | LENGTH         | STANDARD | /L0     | /H0     |
|------------|----------------|----------|---------|---------|
| UNIFIT.001 | 1.2 m / 3000 K | 3675 lm  | 2350 lm | 4550 lm |
| UNIFIT.002 | 1.2 m / 4000 K | 3900 lm  | 2400 lm | 4700 lm |
| UNIFIT.003 | 1.5 m / 3000 K | 5250 lm  | 4300 lm | 6425 lm |
| UNIFIT.004 | 1.5 m / 4000 K | 5275 lm  | 4300 lm | 6600 lm |

Output and colour values are source data.

## 02 Configure Uni-Fit

OUTPUT, CONTROL, EMERGENCY, SENSOR AND SUSPENSION CHOICES ARE SOURCE-LISTED.

| AVAILABLE OPTION DETAILS                                                            |                                                                                     |                                                                                     |                                                                                     | CONTROL / EMERGENCY |                                | SENSOR / SUSPENSION |                                |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|---------------------|--------------------------------|---------------------|--------------------------------|
|  |  |  |  | /ECO / /BTC         | DALI, SwitchDIM, DSI / Casambi | /S0 / /SD           | On/off / 10% dim motion sensor |
| /L0<br>Output                                                                       | /H0<br>Output                                                                       | /ECO<br>Control                                                                     | /EMI<br>Emergency                                                                   | /EMI / /EMP         | Integral emergency indicators  | UNIFIT.ACC.01       | 4 pos 2 m suspension kit       |

### PRODUCT VARIATIONS

/L0 lower output - /H0 higher output - /ECO and /BTC control gear - /EMI and /EMP emergency - /S0 and /SD sensors.

### DOCUMENT

Technical data  
REV 1

|                                                                      |                                                                           |                                                     |                                     |
|----------------------------------------------------------------------|---------------------------------------------------------------------------|-----------------------------------------------------|-------------------------------------|
| <b>DIFFUSER</b><br>Smooth curved IP44 dust-free wipe-clean diffuser. | <b>BODY</b><br>Powder-coated steel with fixed injection-moulded end caps. | <b>DRIVER</b><br>Integral Tridonic driver platform. | <b>WARRANTY</b><br>5 year warranty. |
|----------------------------------------------------------------------|---------------------------------------------------------------------------|-----------------------------------------------------|-------------------------------------|