

Vega

High- and low-bay pendant luminaire range with efficient PMMA optics and robust suspended installation options.



1,025–4,550
lm

LISTED OUTPUT RANGE

60,000 h


L70/B10 MAINTENANCE

2 m

STANDARD SUSPENSION

UK

MANUFACTURED IN THE UK



SHADE DIAMETER

416 mm

BODY HEIGHT

390 mm

DRAWING REFERENCE

VEGA.001-.008

COLOUR PARTS

Part X / Part Y

01 Output selection

EIGHT SOURCE-LISTED MODEL REFERENCES ACROSS 3000 K AND 4000 K.

MODEL REF.	OUTPUT	COLOUR	POWER	LIFE
VEGA.001	1,025 llm	3000 K	10.0 W	60,000 h L70/B10
VEGA.002	1,400 llm	4000 K	10.0 W	
VEGA.003	1,925 llm	3000 K	20.0 W	
VEGA.004	2,075 llm	4000 K	20.0 W	
VEGA.005	2,700 llm	3000 K	30.0 W	
VEGA.006	2,925 llm	4000 K	30.0 W	
VEGA.007	4,200 llm	3000 K	46.0 W	
VEGA.008	4,550 llm	4000 K	46.0 W	

Output, power and maintenance values are source data.

02 Specify Vega

CONTROL, SUSPENSION, EMERGENCY AND FINISH CHOICES ARE SOURCE-LISTED.

CONTROL & SUSPENSION	EMERGENCY	PRODUCT VARIATIONS
/T+DALI Touch dimming / DALI /5M 5 m suspension kit	CONTACT SALES Emergency conversions	CONTACT SALES Any RAL colour /BB / /GG / /WB Black / grey / white combinations

SPECIFICATION OPTIONS

Control, suspension, emergency and finish choices for Vega.

DOCUMENT

Technical data
REV 4 / MAY 2026

ENGINE Philips DLM LED and Xitanium driver.	OPTICS High-efficiency clear PMMA refractor.	MOUNTING Standard 2 m suspension arrangement.	ORIGIN Manufactured in the UK.
---	--	---	--