

Versi

Professional high-output LED downlight with interchangeable reflectors, control options and emergency variants.




1,025–4,550 lm
LISTED OUTPUT

9.5–46.5 W
LISTED POWER

3000 / 4000 K
LED COLOUR

60,000 h+
NOMINAL RATED LIFE



CUT-OUT
176 mm diameter

BEZEL
195 mm diameter

BODY DEPTH
112 mm

SELECTED VARIANT
132 mm depth

01 Output selection

EIGHT SOURCE-LISTED SELECTIONS ACROSS FOUR POWER STEPS.

3000 K OUTPUT	4000 K OUTPUT	POWER	EFFICACY	SELECTION
1,025 lm	1,100 lm	9.5 W	108 / 116 lm/tcW	Source-listed
1,750 lm	1,900 lm	17.5 W	100 / 109 lm/tcW	Source-listed
2,700 lm	2,925 lm	30.0 W	90 / 98 lm/tcW	Source-listed
4,200 lm	4,550 lm	46.5 W	90 / 98 lm/tcW	Source-listed

Output, power and efficacy values are source data.

02 Configure Versi

REFLECTOR, CONTROL AND EMERGENCY CHOICES ARE SOURCE-LISTED.

AVAILABLE OPTION DETAILS	REFLECTOR / CONTROL	EMERGENCY
 /MF50 Reflector  /SP40 Reflector Touch Dimming OR DALI  /T-DALI Control CASAMBI  /BTC Control  /EM Emergency	/MF50 / /SP40 Multi-facet / specular reflector /T-DALI / /BTC DALI or Casambi control	/EM / /EMD Remote indicator options /EMI / /EMDI Integral indicator options
 /EMD Emergency  /EMI Emergency  /EMDI Emergency		

PRODUCT VARIATIONS

Reflector, control, IP65 and emergency variants.

DOCUMENT

Technical data
REV 1

OPTICS 60 degree satin etched aluminium reflector as standard.	SYSTEM Philips LED module and driver system.	PROTECTION IP54 and IP65 options.	APPLICATION Commercial interiors requiring flexible optical control.
--	--	---	--