

Void

Large-diameter low-glare LED downlight for shallow ceiling voids, with a compact recessed body and source-listed control, emergency and ingress options.




1,150–5,300 lm
LISTED OUTPUT

9.5–44.5 W
LISTED POWER

Up to 133 lm/tcW
LUMINAIRE EFFICACY

60,000 h L90/B10
RATED LIFE



CUT-OUT
222 mm

BEZEL
232 mm

BODY HEIGHT
160 mm

CEILING VOID
>500 mm min.

01 Output selection

FIVE SOURCE-LISTED OUTPUT AND POWER PAIRINGS AT 3000 K / 4000 K.

LED COLOUR	OUTPUT	POWER	LUMINAIRE EFFICACY
3000 K / 4000 K	1,150 / 1,200 lm	9.5 W	121 / 126 lm/tcW
3000 K / 4000 K	1,825 / 1,900 lm	14.5 W	126 / 131 lm/tcW
3000 K / 4000 K	3,100 / 3,250 lm	24.5 W	127 / 133 lm/tcW
3000 K / 4000 K	4,500 / 4,700 lm	37 W	122 / 127 lm/tcW
3000 K / 4000 K	5,100 / 5,300 lm	44.5 W	115 / 119 lm/tcW

Output and power values are source data.

02 Configure Void

CONTROL, EMERGENCY, INGRESS AND HIGH-CRI CHOICES ARE SOURCE-LISTED.

AVAILABLE OPTION DETAILS

/ECO Control

/BTC Control

/EM Emergency

/EMP Emergency

/EMI Emergency

/EMPI Emergency

/54 Ingress

/R9 High CRI

CONTROL / OPTICAL

/ECO SwitchDIM / DALI / DSI control

/BTC Casambi wireless control

/R9 High colour-rendering option

EMERGENCY / INGRESS

/EN / /EMP One-hour emergency options

/EMI / /EMPI Three-hour emergency options

/54 IP54 protection option

PRODUCT VARIATIONS
Control, emergency, ingress and high-CRI choices.

DOCUMENT
Technical data
MAY 2026

OPTICS Low-glare multi-faceted aluminium reflector.	SYSTEM Tridonic LED module and driver.	PERFORMANCE Up to 133 lm/tcW luminaire efficacy.	APPLICATION Large-diameter downlight for shallow ceiling voids.
---	--	--	---