

BULKHEADS / IP54 / IK10 / WALL OR CEILING MOUNTED

Titan

Robust circular LED bulkhead for practical industrial and commercial interiors.

Titan is designed for projects that need a durable circular bulkhead with a simple surface-mounted form, broad distribution and a shallow 58 mm body depth. The 300 mm diameter format gives the fitting a clean ceiling or wall presence while keeping specification and installation straightforward.

Technical data lists an IP54 and IK10 rated construction, opal TP(a) polycarbonate diffuser, SMD LED platform with integral driver, switchable colour temperature and 180 degree light distribution. It is suited to back-of-house, circulation, plant, utility and general commercial areas where a robust, low-maintenance luminaire is required.



TITAN CIRCULAR LED BULKHEAD, 300 MM DIAMETER.

 <p>IP54 rated Protected for practical internal commercial and industrial use.</p>	 <p>IK10 impact Robust bulkhead construction for higher-impact locations.</p>	 <p>180 degree output Broad distribution through an opal TP(a) polycarbonate diffuser.</p>	 <p>Integral LED SMD LED platform with integral driver listed in data.</p>	 <p>Switchable CCT Selectable 3000K, 4000K and 5500K colour temperatures.</p>	 <p>Wall or ceiling Suitable for ceiling or wall mounting applications.</p>
--	---	--	--	---	---

Key Features

- + Robust circular LED bulkhead for commercial and industrial interiors
- + 180 degree light distribution for broad general illumination
- + SMD LED and integral driver platform
- + Ceiling or wall mounted installation
- + IP54 ingress protection and IK10 impact rating
- + Opal TP(a) polycarbonate diffuser
- + Switchable 3000K, 4000K and 5500K colour temperature

Technical Snapshot

Model references	TITAN.001 to TITAN.001
Delivered output	2700 llm
Power	25 tcw
Colour temperature	3000K / 4000K / 5500K
Ingress rating	IP54
Impact rating	IK10
Life rating	50,000h L70/B50
Mounting	Ceiling or wall

Project Fit

- + Use where a durable bulkhead is needed for utility, circulation, plant, back-of-house or ancillary commercial spaces.
- + Selection reference TITAN.001 covers the 2700 llm, 25 tcW, switchable CCT configuration.
- + For emergency or sensor versions, specify through the Sentinel or Harbor bulkhead ranges.

Specification Data

Technical dimensions, model reference and project notes for Titan schedules.

REV2 / MAY 2026
LL-TITAN-DS

Technical Drawing

300 MM DIAMETER AND 58 MM DEPTH SHOWN IN THE DRAWING.

Diameter	Depth
300 mm	58 mm

Ordering Information

MODEL REFERENCE

DELIVERED OUTPUT (LLM)	ABSOLUTE POWER (TCM)	COLOUR TEMPERATURE K	MODEL REFERENCE
2700	25	3000K, 4000K, 5500K	TITAN.001

Specification Notes

CONTROLS AND EMERGENCY

EMERGENCY OR SENSOR REQUIREMENTS	MOUNTING	COLOUR TEMPERATURE
Use Sentinel or Harbor bulkhead ranges	Ceiling or wall mounted	Switchable 3000K / 4000K / 5500K

+ data lists one model reference for Titan.

+ Emergency and sensor variants are specified through the Sentinel or Harbor bulkhead ranges.

	CE		DC	Declaration of Conformity available
--	----	--	----	-------------------------------------

Please note: Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25 deg C. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/-10%. We reserve the right to amend or change details without prior notification. E5DE.