150 Series Datasheet




LUMENL∞P





Technical Drawing



Options

Please select from the options below.

Black	/ВК
Dimming	/DALI
Narrow beam 19.6°	/NB
Wide beam 36.2°	/WB
High colour rendering Ra90	/9
Excite 100K Driver	/ТОР

Key Features

- A contemporary track spotlight with vertical gear housing
- Swivel and tilt adjustment for added flexibility
- High colour rendering option
- Medium beam reflector (25.6°) as standard, other beam options available
- Compatible with Global Trac, Stucchi and Eutrac systems
- Short circuit, overload and temperature protection
- Life >55,000 hours L70 / F10
- White as standard, black is also available
- Dimming option

Ordering Information

Colo	put Power tcW	Luminaire Ou Ilm
830	10	1100
930	10	925
840	10	1175
940	10	975
830	20.5	1975
930	20.5	1625
840	20.5	2075
940	20.5	1750

Please note: Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25°C. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/-10%. We reserve the right to amend or change details without prior notification. E&OE. MDS-194D-REV3 06/01/2023

150 Series Datasheet



Options



/NB Narrow beam reflector 19.6°



/WB Wide beam reflector 36.2°



/TOP Tridonic Excite driver - 100,000 hours I-Select, loop in - loop out



/BK Black



High colour rendering See technical



9000/BP-D-W Surface mounting pattress - White



/DALI Dimming



9000/BP-D-B Surface mounting pattress - Black

Also Available



Product variations Other colours and specifications available on request



Horizontal gear housing See 151 Series datasheet



Track See Stucchi ONETRACK datasheet