


Key Features

- Continuous direct, extruded linear profile system
- Features through wiring for simple electrical connection
- Mechanical joining kit with every product
- Start / End piece includes end cap
- Available in 4 building block lengths
- Delivering approx. 2200 llm/m as standard
- Suitable for surface mount or suspension fixing
- Finished in RAL 9006 grey as standard
- ▶ TPa opal lens for general and visual areas as standard
- ▶ Low glare prismatic lens available for office and LG7 compliance
- Tridonic low energy LED and driver system
- Life up to >72,000 hours L80/F10
- Manufactured in the U.K.

Ordering Information

Length	Colour	Luminaire Output (Ilm) Std	Intermediate Model Ref.	Luminaire Output (Ilm) /L0	Luminaire Output (Ilm) /HO
850 mm	830	1725	173.001	1175	2725
850 mm	840	1825	173.002	1225	2875
1.2 m	830	2575	173.003	1750	4100
1.2 m	840	2725	173.004	1850	4300
1.5 m	830	3150	173.005	2150	5000
1.5 m	840	3325	173.006	2250	5250
2.5 m	830	5150	173.007	3500	8175
2.5 m	840	5425	173.008	3675	8575

Technical Drawing















Declaration of Conformity available

Options

Please select from the options below.

Start and End body c/w end cap	/SE
White body	/WH
Black body	/BK
Lower output	/LO
Higher output	/H0
Low glare prismatic lens for LG7 compliance	/LG
SwitchDIM, DALI or DSI	/ECO
EM conversion (not 173.001 / 174.002)	/EMI
Suspension kit	/SUS

173 Series Options and Accessories




Options




/SE Start / end section with end cap




/WHWhite body



/BKBlack body




/LOLower output



/HO Higher output



/LGLow glare prismatic lens




/ECOSwitchDIM, DALI or DSI




/EMI EM conversion (not 173.001 / 173.002)


Accessories



SUS.163/2/2M 2M 2pcs suspension kit (not 2.5 m)



SUS.163/3/2M 2M 3pcs suspension kit (for 2.5 m)



Product variationsCustom colours



PT001 Diffuser removal tool