


Key Features

- Continuous direct/indirect linear profile system
- ▶ Features through wiring for simple electrical connection
- Mechanical joining kit with every product
- Start / End piece includes end cap
- ► Typical percentage output ratio 75:25
- Finished in RAL 9006 grey as standard
- Available in 3 building block lengths
- ▶ Delivering approx. 2200 llm/m as standard
- ► TPa opal lens for general and visual areas as standard
- ▶ Low glare prismatic lens available for office and LG7 compliance
- ▶ Tridonic low energy LED and driver system
- ► Lumen maintenance L80/F10 @ >72,000 hours
- Efficacy up to 130 llm/tcW
- Manufactured in the U.K.
- 2 m suspension kit

Ordering Information

Length	Colour	Luminaire Output (IIm) Std	Model Ref.	Luminaire Output (Ilm) /L0	Luminaire Output (Ilm) /HO
850 mm	830	2300	174.001	1550	3650
850 mm	840	2400	174.002	1625	3825
1.2 m	830	3450	174.003	2325	5475
1.2 m	840	3600	174.004	2450	5725
1.5 m	830	4450	174.005	3000	7050
1.5 m	840	4650	174.006	3150	7375

Technical Drawing















Declaration of Conformity available

Options

Please select from the options below.

Start / End section with end cap	/SE
White body	/WH
Black body	/BK
Lower output	/L0
Higher output	/H0
Low glare prismatic lens for LG7 compliance	/LG
SwitchDIM, DALI or DSI	/ECO
EM conversion (not 174.001 / 174.002)	/EMI

174 Series Options and Accessories


Options




/SE Start / end section with end cap




/WH White body



/BK Black body




/LOLower output



/HO Higher output



/LGLow glare prismatic lens



/ECO SwitchDIM, DALI or DSI




/EMI EM conversion (not 174.001 / 174.002)

Also Available



Product variationsOther colours and specifications available on request



Product variationsCustom body colours



Product variationsCustom colours



PT001 Diffuser removal tool