




Key Features

- MINI high output, low glare LED gimbal
- Fully adjustable die cast body
- Philips LED and driver system
- Premium White Ra90 LED module as standard
- 24° reflector as standard with 12° and 40° options
- No visible flicker (IEEE 1789 2015)
- ▶ ETL and Part L compliant variants
- Life >50,000h L70/B10
- ▶ 5 year warranty

Technical Drawing

















Declaration of Conformity available

Ordering Information

Luminaire Output	Power	Colour	Model Ref.
llm	tcW		
975	10	930	180.001
1050	10	940	180.002
1650	16.5	930	180.003
1775	16.5	940	180.004
2450	27	930	180.005
2650	27	940	180.006

Options

Please select from the options below.

/NB	12° multi- faceted reflector	
/WB	40° multi- faceted reflector	
/T+DALI	Touch dimming / DALI	
/BTC	Casambi wireless network (inc dim)	
/EM	Emergency (remote indicator)	
/EMD	DALI Emergency (remote indicator)	
Contact Sales	Black body	

180 Series Options and Accessories

Options



/NB 12° Multi- faceted reflector



/WB 40° Multi- faceted reflector



Contact Sales Black body



/T+DALI
Touch dimming / DALI



/BTC Casambi Bluetooth wireless network (inc dim)



/EM
3h EM conversion
c/w remote indicator



JEMD
3h DALI / ST EM conversion
c/w remote indicator