# 94 Series Datasheet






## Key Features

- Incorporating the Philips Fortimo DLM Flex and Xitanium driver
- High efficiency clear PMMA refractor
- 2 m suspension kit as standard, 5 m option available
- Dimming options
- Colour combinations available for gear housing
- Life up to >60,000 hours (L70/B10)
- Emergency options available

#### Technical Drawing



#### Ordering Information

Luminaire Output Ilm	Power tcW	Colour	Model Ref.
1025	10	830	94.1100.30
1100	10	840	94.1100.40
1925	20	830	94.2000.30
2075	20	840	94.2000.40
2700	30	830	94.3000.30
2925	30	840	94.3000.40
4200	46	830	94.5000.30
4550	46	840	94.5000.40

#### Options

Please select from the options below.

Touch dimm	ing / DALI	/T+DALI	
5 m suspension kit			/5M
<b>W</b> = White	<b>B</b> = Black	<b>G</b> = Grey	Part X
<b>W</b> = White	<b>B</b> = Black	<b>G</b> = Grey	Part Y

Please note: Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25°C. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/-10%. We reserve the right to amend or change details without prior notification. E&OE. MDS-124D-REV9 11/10/2022

# 94 Series Options and Accessories

## Options




**/T+DALI** Touch dimming / DALI



**/5M** 5 m suspension kit



**Emergency conversions** Contact Sales



Any RAL colour Contact Sales

#### **Code examples**



**/BB** Black, Black



**/GG** Grey, Grey



/WB White, Black