

The ONETRACK's are made of extruded aluminium with PVC insulation, copper conductors, and an integrated DATABUS. They come in different colours depending on the model.

GENERAL DATA

Description: Three-circuit surface track with two additional conductors intended to manage a general data signal (DALI, DMX, LON, EIB and others) Body: extruded aluminium Colour: black (B), RAL9005 Conductor: cooper, isolated in PVC profile Lengths: 1000 mm

Environment	Indoor
Application	retail, public place, showroom, museum, exhibition, residential

ELECTRICAL DATA

Mains voltage: 220-240V, 50/60Hz

LIGHTING DATA


TECHNICAL DATA

Net weight, kg: 1.1
Dimensions, mm: 1000x31x38

STANDARDS

Protection class IEC: I **Ingress protection code:** IP20
Certificates: CE, RoHS, ENEC

Technical drawing (.jpg)



Code	Application	Length	Color
9000A-1/B-ST	Surface/suspended	1000 mm	Black
9000A-1/B-STSurface/suspendedView productELECTRIFIED 6-CONDUCTOR TRACK FOR CEILING/WALL OR SUSPENSION MOUNTING			
9000A-1/G-ST	Surface/suspended	1000 mm	Anodizzato
9000A-1/W-ST	Surface/suspended	1000 mm	White
9000A-2/B-ST	Surface/suspended	2000 mm	Black
9000A-2/G-ST	Surface/suspended	2000 mm	Anodizzato
9000A-2/W-ST	Surface/suspended	2000 mm	White
9000A-3/B-ST	Surface/suspended	3000 mm	Black
9000A-3/G-ST	Surface/suspended	3000 mm	Anodizzato
9000A-3/W-ST	Surface/suspended	3000 mm	White
9000A-4/B-ST	Surface/suspended	4000 mm	Black
9000A-4/G-ST	Surface/suspended	4000 mm	Anodizzato
9000A-4/W-ST	Surface/suspended	4000 mm	White

ORDERING INFORMATION

Description	Model Ref. White	Model Ref. Black
1 m track	9000A-1/W-ST	9000A-1/B-ST
2 m track	9000A-2/W-ST	9000A-2/B-ST
End feed	9001/W	9001/B
Straight connector	9003/W	9003/B
End cap	9004/W	9004/B
L-connector / feed	9011/W	9011/B
Flexible adjustable corner connector	9018/W	9018/B
2 m wire suspension kit	S-9000/114-T/W	S-9000/114-T/B
Patress	9000/BP-D-W	9000/BP-D-B