Aero

Compact commercial downlight with three selectable LED colour temperatures.




672 lm
LUMINAIRE OUTPUT

9 W
LUMINAIRE POWER

Ra 80
COLOUR RENDERING

IP54 / IP20
FRONT / REAR PROTECTION

DIMENSIONS



LED COLOUR
3000 / 4000 / 5500 K

FACTORY DEFAULT
4000 K

GLARE RATING
UGR 21.9

RATED LIFE
L70/B50 50,000 h

01 Output selection

ONE 9 W OUTPUT WITH THREE SELECTABLE LED COLOUR TEMPERATURES.

MODEL	OUTPUT	POWER	EFFICACY	LED COLOUR	PROTECTION
35.001	672 lm	9 W	75 lm/W	3000 / 4000 / 5500 K	IP54 front / IP20 rear

Factory default colour temperature: 4000 K.

02 Technical performance

PERFORMANCE VALUES FOR MODEL 35.001.

OPTICAL	
OUTPUT	672 lm
CRI	Ra 80
QUALITY	SDCM 6

ELECTRICAL	
POWER	9 W
SUPPLY	220–240 V
FREQUENCY	50–60 Hz

OPERATING	
TEMP.	-25 to +25 °C
WEIGHT	0.26 kg
WARRANTY	3 years

COLOUR SELECTION
3000 K · 4000 K · 5500 K. Factory default is 4000 K.

DOCUMENT
Technical data
REV 2

OPTICAL
672 lm output, 75 lm/W efficacy and UGR 21.9.

PROTECTION
IP54 protection from the front and IP20 at the rear.

ELECTRICAL
9 W at 220–240 V and 50–60 Hz.

RATED LIFE
L70/B50 50,000 hours.

Figures are provided for product selection. Details may change without notice. E&OE.

02045 721 554
INFO@LUMENLOOP.CO.UK
LUMENLOOP.CO.UK