COMMERCIAL LIGHTING / RECESSED / ADJUSTABLE

Glance

Low-glare adjustable scoop downlight for directional recessed lighting.

TECHNICAL DATA
LL-GLANCE-DS
REV 2 / OCT 2026




1150–2800 lm
STANDARD OUTPUT

8.0–19.0 W
SYSTEM POWER

3000 / 4000 K
LED COLOUR

355° / 70°
SWIVEL / TILT



BEZEL
150 mm

CUT-OUT
140 mm

ABOVE CEILING
130 mm max

BELOW CEILING
105 mm max

01 Output selection

SIX MODEL REFERENCES ACROSS THREE OUTPUT AND POWER STEPS.

MODELS	OUTPUT	POWER	LED COLOUR	ADJUSTMENT
GLANCE.001 / .002	1150 / 1175 lm	8.0 W	3000 / 4000 K	355° / 70°
GLANCE.003 / .004	1950 / 2025 lm	13.5 W	3000 / 4000 K	355° / 70°
GLANCE.005 / .006	2725 / 2800 lm	19.0 W	3000 / 4000 K	355° / 70°

Output, power and colour values are source data.

02 Configure Glance

REFLECTOR, CONTROL AND EMERGENCY SUFFIXES ARE AVAILABLE FOR SELECTION.

AVAILABLE OPTION DETAILS


/NB
Narrow beam



/WB
Wide beam



/T+DALI
Control



/BTC
Casambi



/EMD
Emergency

REFLECTOR / CONTROL

/NB	12 degree reflector
/WB	40 degree reflector
/T+DALI / /BTC	Control options

EMERGENCY

/EM	Emergency remote indicator
/EMD	DALI emergency remote indicator
/EMS	Self-test, remote indicator

PRODUCT VARIATIONS
/NB narrow beam · /WB wide beam · /T+DALI touch dimming / DALI · /BTC Casambi · /EM emergency · /EMD DALI emergency.

DOCUMENT
Technical data
REV 2 / OCT 2026

BODY
Adjustable die-cast scoop body.

REFLECTOR
24 degree standard reflector; 12 and 40 degree alternatives.

LED
Ra80 LED module; /R9 Ra90 option.

CONTROL
Touch dimming, DALI and wireless control options.

Figures and options are provided for product selection. Details may change without notice. E&OE.

02045 721 554
INFO@LUMENLOOP.CO.UK
LUMENLOOP.CO.UK