EXIT SIGNS / RECESSED / DOUBLE SIDED

Recessed Exit Sign

Recessed double-sided LED exit sign with EU and ISO legend options.

TECHNICAL DATA
LL-RECESSEDEXITSIGN-DS
REV 1 / JUNE 2026



3 hours
RATED EMERGENCY DURATION

EU / ISO
LEGEND-PANEL OPTIONS

/EMD
DALI / SELF-TEST OPTION

Recessed
CEILING CUT-OUT FORMAT



BEZEL
355 × 112 mm

CUT-OUT
335 × 95 mm

LEGEND HEIGHT
150 mm

LEGEND PANEL
288 mm

01 Ordering information

ONE SOURCE-LISTED MODEL WITH FIXED FINISH, DURATION, RECHARGE AND LIFETIME.

MODEL REF.	FINISH	DURATION	RECHARGE	LIFETIME
RECESSEDEXITSIGN.001	White	3 hours	24 hours	50,000 hours

The governed sheet does not list lumen output, system power, colour temperature or product efficacy.

02 Specify Recessed Exit Sign

LEGEND, CONTROL AND SIGNAGE CHOICES ARE SOURCE-LISTED.

CONTROL

/EMD	DALI / self-test version

LEGEND PANELS

EU	LXSLR, LXSUP
ISO	LXSAD/ISO, LXSLR/ISO, LXSUP/ISO

SIGNAGE

CUSTOM	Custom designed signage
STANDARD	Arrow-down legend panel

SPECIFICATION OPTIONS
Control, EU or ISO legend panels and custom designed signage.

DOCUMENT
Technical data
REV 1 / JUNE 2026

EMERGENCY
3 hour rated duration.

OPERATION
Maintained or non-maintained.

ILLUMINATION
15 high-intensity LEDs.

CERTIFICATION
UKCA, CE and DC declaration.

Figures and options are provided for product selection. Details may change without notice. E&OE.

02045 721 554
INFO@LUMENLOOP.CO.UK
LUMENLOOP.CO.UK